



PORTABLE ADSORPTION DEHUMIDIFICATION

**AD 200-300-400**

IDEAL FOR DRYING AT LOW TEMPERATURES IN CONSTRUCTION, WATER  
DAMAGE AND WATERWORKS INDUSTRIES







# INDEX

<b>Introduction</b>	
Ensuring dry conditions at low temperatures	4
<b>AD 200</b>	
Adsorption dehumidifier	6
<b>AD 300</b>	
Adsorption dehumidifier	8
<b>AD 400</b>	
Adsorption dehumidifier	10

# ENSURING DRY CONDITIONS AT LOW TEMPERATURES

Adsorption dehumidification ensures dry conditions at low temperatures. This makes the AD portable range the obvious choice for drying out new buildings or water damage during the winter season and for maintaining low levels of relative humidity at facilities with a low ambient temperature.

Humidity problems are most often associated with hot and damp environments, and usually a condense drying dehumidifier is applied. However, at ambient temperatures below 10°C condensation is not very easily achieved, whereas humid air and moisture from materials, open water surfaces, and production processes can cause serious damage at even very low temperatures.

The AD portable range offers reliable control of the relative humidity of the air, and drying out water damage or newly constructed buildings even at winter temperatures. – After all, accidents happen regardless of the seasons, and construction work goes on all the year round.

## Sturdy and compact design

The portable units have been designed for easy handling and transportation. The sturdy stainless steel cabinets are surprisingly compact and low weight compared to capacity. The countersunk control panel is well protected and folding handles for carrying make the units easy to stack during transportation and storage.

## Key features

- Ensures dry conditions at low temperatures
- Reliable control of the relative humidity of the air
- Sturdy and compact design
- Cabinet in stainless steel/hot galvanized powder coated steel
- Designed for easy handling and transportation
- Low weight
- Easy to stack during transportation and storage
- MID approved energy counter (optional with AD 400)
- Hour counter
- Internal hygostat (AD 400: connection for external hygostat)



**AD 200**



**AD 300**



**AD 400**



# ENSURING DRY CONDITIONS AT LOW TEMPERATURES

## Easy installation and service

The portable units are fast and easy to install. Just connect one or two hoses to the dry air and one hose to the regeneration air outlet and lead it to the outside. The cabinet provides easy access for internal cleaning and service, and the air filter can be changed without opening the cabinet.


## High-performance operations

The built-in hour and energy counter shows the accumulated hour and energy consumption. The energy counter of the AD 200/AD 300 is very precise and has the MID approval which is highest marked standard. The portable range offers reliable high-performance operations at low temperatures and easy installation ensure fast results in drying out constructions and emergency situations minimizing the long-term damage caused by flooding. The portable units can run continuously, or they can be controlled by internal hygostat with the AD 200/AD 300 or external hygostat with the AD 400.

## How the dehumidifier works

An adsorption dehumidifier is divided into two zones. In the drying zone humid air from the air inlet passes through a silica gel rotor that adsorbs the moisture and the dry air is returned to the room. In the regeneration zone hot air is blown through the rotor drying out the silica gel and carrying the moisture through the connected hose to the outside.

*How an adsorption dehumidifier works*



## Applications



Archives



Cellars



Construction sites



Garages



Production facilities



Warehouses & storage facilities



Waterworks



Water damage restoration

# AD 200



**AD 200**

The AD 200 is a robust compact adsorption dehumidifier with a silica gel rotor as standard. Process air is drawn into the dehumidifier and through the rotor, which slowly turns between two sections in the dehumidifier. The silica gel rotor adsorbs the moisture from the air in the drying section. This moisture is removed again by blowing hot air through the rotor in the regeneration section. The process air leaves the dehumidifier as dry air, and the moisture is led out of the room through the regenerated air outlet.



- MID approved energy counter
- Hour counter
- Internal humidistat
- One common fan for process air and regeneration air
- Cabinet in stainless steel / hot galvanized powder coated steel
- Low weight
- PTC regeneration heater
- Robust and compact metal construction
- Carrying handle
- Easy internal access for service and maintenance
- Four rubber bumpers to fix the unit in place
- Flexible dry air outlet

## Optional accessories




**Spare filter set  
098891**



**Front plate  
098893**


## Performance Data



## PORTABLE ADSORPTION DEHUMIDIFIERS

# AD 200

### Dimensions



Specifications	Units	AD 200
Capacity (20°C/60% RH)	kg/24h	18.75
Air volume – dry air/regeneration air	m <sup>3</sup> /h	210/110
Ext. pressure – dry air/regeneration air	Pa	150/50
Operating temperature range	°C	-10 - +35
Operating humidity range	% RH	10-95
Nominal power consumption	W	694
Power supply	V/Hz	230/1ph/50
Sound level	dB(A)	48
<b>Duct sizes:</b>		
Air inlet	Ømm	125
Dry air outlet	Ømm	1 x 80 or 2 x 50
Regeneration air outlet	Ømm	80
Power cord	m	4.5 with plug
Protection class		IP23
Product size (h x w x d)	mm	285 x 289 x 395 (incl. fittings and feet)
Weight	kg	14

# AD 300



**AD 300**

The AD 300 is a robust compact adsorption dehumidifier with a silica gel rotor as standard. Process air is drawn into the dehumidifier and through the rotor, which slowly turns between two sections in the dehumidifier. The silica gel rotor adsorbs the moisture from the air in the drying section. This moisture is removed again by blowing hot air through the rotor in the regeneration section. The process air leaves the dehumidifier as dry air, and the moisture is led out of the room through the regenerated air outlet.



- MID approved energy counter
- Hour counter
- Internal humidistat
- One common fan for process air and regeneration air
- Cabinet in stainless steel / hot galvanized powder coated steel
- Low weight
- PTC regeneration heater
- Robust and compact metal construction
- Carrying handle
- Easy internal access for service and maintenance
- Four rubber bumpers to fix the unit in place
- Flexible dry air outlet

## Optional accessories




**Spare filter set  
098892**



**Front plate  
098894**

## Performance Data






## PORTABLE ADSORPTION DEHUMIDIFIERS

# AD 300

### Dimensions



Specifications	Units	AD 300
Capacity (20°C/60% RH)	kg/24h	25.7
Air volume – dry air/regeneration air	m <sup>3</sup> /h	300/110
Ext. pressure – dry air/regeneration air	Pa	150/50
Operating temperature range	°C	-10 - +35
Operating humidity range	% RH	10-95
Nominal power consumption	W	1,040
Power supply	V/Hz	230/1ph/50
Sound level	dB(A)	57
<b>Duct sizes:</b>		
Air inlet	Ømm	125
Dry air outlet	Ømm	1 x 100 or 2 x 50
Regeneration air outlet	Ømm	80
Power cord	m	4.5 with plug
Protection class		IP23
Product size (h x w x d)	mm	352 x 337 x 429 (incl. fittings and feet)
Weight	kg	18

## PORTABLE ADSORPTION DEHUMIDIFIERS

# AD 400



**AD 400**

Despite weighing out at just 25 kilos, the AD 400 is the right choice for applications that require an air change of up to 480m<sup>3</sup>/h (environments of up to 450m<sup>3</sup>). That's 20% more than other units of comparable size that are currently on the market. With its integrated lifting handle and stackable design, the unit has been designed for easy handling and transportation. It comes with a built-in hour counter with an optional MID-approved energy counter. The portable adsorption dehumidifiers can run continuously, or they can be controlled by an external hygrostat.



- Ventilation only mode available – if pre-set humidity level is exceeded, normal dehumidification mode starts (only with optional external hygrostat)
- Sturdy unit made of stainless steel and powder coated sheet steel, supported by four rubber non-marking feet
- Integrated lifting handle and stackable design for easy use
- The rotor unit is easy to remove for cleaning purpose
- Dynamic, safe and self-regulating PTC heating element
- Energy-efficient radial fan
- High-performance ECODRY G3-MH rotor for maximum water absorption
- Air filter on the process air inlet
- Noise reduced via integrated silencer: 60 dB
- Connection for external hygrostat
- Non-resettable hour counter



### Optional accessories



**Spare filter set**  
098895




**External hygrostat**  
351036

## PORTABLE ADSORPTION DEHUMIDIFIERS

# AD 400

### Dimensions



Specifications	Units	AD 400
Capacity (20°C/60% RH)	kg/24h	36
Air volume – dry air/regeneration air	m <sup>3</sup> /h	480/185
Ext. pressure – dry air/regeneration air	Pa	150/100
Operating temperature range	°C	-10 - +35
Operating humidity range	% RH	10-95
Nominal power consumption	W	2,200
Power supply	V/Hz	230/1ph/50
Sound level	dB(A)	60
<b>Duct sizes:</b>		
Dry air outlet	Ømm	125
Regeneration air outlet	Ømm	80
Power cord	m	4.5 with plug
Protection class		IP23
Product size (h x w x d)	mm	410 x 395 x 560
Weight	kg	25

**Dantherm A/S**

Marienlystvej 65  
DK-7800 Skive  
Denmark  
t. +45 96 14 37 00

**Dantherm Ltd.**

Unit 12, Galliford Road  
Maldon CM9 4XD  
United Kingdom  
t. +44 (0)1621 856611

**Dantherm GmbH**

Oststraße 148  
22844 Norderstedt  
Germany  
t. +49 40 526 8790

**Dantherm S.p.A.**

Via Gardesana 11  
37010 Pastrengo (VR)  
Italy  
t. +39 045 6770533

**Dantherm Sp. z o.o.**

ul. Magazynowa 5a  
62-023 Gądk  
Poland  
t. +48 61 65 44 000

**Dantherm SP S.A.**

C/Calabozos 6  
(Polígono Industrial)  
28108 Alcobendas, Madrid  
Spain  
t. +34 91 661 45 00

**Dantherm SAS**

23 rue Eugène Hénaff  
69694 Vénissieux Cedex  
France  
t. +33 4 78 47 11 11

**Dantherm AS**

Løkkeåsveien 26  
3138 Skallestad  
Norway  
t. +47 33 35 16 00

**Dantherm AB**

Fridhemsvägen 3  
602 13 Norrköping  
Sweden  
t. +46 (0)11 19 30 40

**Dantherm LLC**

Transportnaya 22/2  
142800, Stupino  
Moscow  
Russia  
t. +7 (495) 642 444 8

**MCS China**

Unit 2B, No. 512  
Yunchuan Road  
Baoshang, Shanghai, 201906  
China  
t. +8621 61486668

**AirCenter AG**

Täferstrasse 14  
CH-5405 Baden Dättwil  
Switzerland  
t. +41 43 500 00 50

**Heylo GmbH**

Im Finigen 9  
28832 Achim  
Germany  
t. +49 4202 97550

**SET Energietechnik GmbH**

August-Blessing-Straße 5  
71282 Hemmingen  
Germany  
t. +49 7150 94540

Dealer:

KEEP UPDATED  
**FOLLOW US ON:**



[danthermgroup.com](http://danthermgroup.com)