



DEHUMIDIFICATION SOLUTIONS FOR DRYING ROOMS

## **CD 15**

THE VERSATILE SOLUTION FOR YOUR DEHUMIDIFICATION CHALLENGES

## WALL-MOUNTED DEHUMIDIFIERS

# CD 15

The CD 15 is compact, lightweight, robust and quiet. It incorporates a bracket to enable fast and simple wall mounting of the solution. Powerful and highly efficient, it constitutes a great and versatile solution for a number of different dehumidification tasks.



**CD 15**

Applications include:

- Waterworks
- Car storage
- Museum and gallery preservation
- Storage, preservation, and archives
- Small commercial applications
- Homes and small offices



- Built into a strong and brushed stainless steel cabinet
- Built-in hygostat
- Operating hour counter
- Easy accessible air filters from front cover
- Reciprocating compressor
- F-gas directive compliant
- Energy efficient axial fan
- Electronic control and user-friendly display panel
- Active, demand-controlled defrosting
- Automatic pump-out with overflow protection
- Wall bracket included

Specifications	Units	CD 15
Operating temperature range	°C	5-30
Operating humidity range	% RH	40-100
Dehumidification @ 30°C/80% RH	l/24h	15.0
Dehumidification @ 20°C/60% RH	l/24h	8.5
Air flow	m³/h	225
Power supply	V/Hz	230/1ph/50
Max. power consumption	kW	0.3
Sound pressure level @ 1m	dB(A)	46
Refrigerant		R1234yf
Product size (w x d x h)	mm	330 x 280 x 490
Weight	kg	18.5

## Electronic control




The CD 15 has a built-in hygrostat and is fully automatic with electronic control.

- LED for "Pump error"
- LED for "Temperature warning"
- LED for Relative humidity OK"

## Defrosting


Active, demand-controlled defrosting is incorporated in the electronic control. A sensor on the evaporator coil ensures that the evaporator is only defrosted when required. The evaporator coil is defrosted by means of hot refrigerant bypassing the condenser and being fed through the evaporator.

## Automatic pump-out



The product is serially equipped with an automatic pump-out with overflow protection.

## Optional accessories





**Replacement air filter**  
490146



**Condensate drainage hose**  
490100  
12 x 2mm

## CD 15 dimensions



All measurements are in mm  
Dimensions above include external fittings



**Dantherm A/S**

Marienlystvej 65  
DK-7800 Skive  
Denmark  
t. +45 96 14 37 00

**Dantherm Ltd.**

Unit 12, Galliford Road  
Maldon CM9 4XD  
United Kingdom  
t. +44 (0)1621 856611

**Dantherm GmbH**

Oststraße 148  
22844 Norderstedt  
Germany  
t. +49 40 526 8790

**Dantherm S.p.A.**

Via Gardesana 11  
37010 Pastrengo (VR)  
Italy  
t. +39 045 6770533

**Dantherm Sp. z o.o.**

ul. Magazynowa 5a  
62-023 Gądk  
Poland  
t. +48 61 65 44 000

**Dantherm AS**

Løkkeåsveien 26  
3138 Skallestad  
Norway  
t. +47 33 35 16 00

**Dantherm AB**

Fridhemsvägen 3  
602 13 Norrköping  
Sweden  
t. +46 (0)11 19 30 40

**Dantherm AG**

Im Vorderasp 4  
8154 Oberglatt ZH  
Switzerland  
t. +41 44 851 51 51

**Dantherm SP S.A.**

C/Calabozos  
6 (Polígono Industrial)  
28108 Alcobendas, Madrid  
Spain  
t. +34 91 661 45 00

**Dantherm LLC**

Transportnaya 22/2  
142800, Stupino  
Moscow  
Russia  
t. +7 (495) 642 444 8

**Dantherm SAS**

23 rue Eugène Henaff  
69694 Vénissieux Cedex  
France  
t. +33 4 78 47 11 11

**MCS China**

Unit 2B, No. 512  
Yunchuan Road  
Baoshang, Shanghai, 201906  
China  
t. +8621 61486668

Dealer: