



## **ASE 400 ADSORPTION AIR DEHUMIDIFIER**

UNMATCHED DEHUMIDIFICATION PERFORMANCE IN ITS CLASS

## PORTABLE DRYING

# HIGH-PERFORMANCE ADSORPTION DRYER FOR LOW TEMPERATURE AREAS



### ASE 400

Ideally suited for dehumidification of large spaces with low temperatures, the portable ASE 400 is an extremely compact, sturdy and light-weight adsorption dryer. Due to its high-performance at low temperatures, the easily installed ASE 400 will deliver fast results in drying out all kinds of construction and emergency situations, thereby minimising the risk of long-term damage caused by for instance flooding. Application examples include cellars, garages, warehouses, storage rooms, archives, production facilities, waterworks and more.



### Benefits

- 20% higher air capacity than similar units on the market
- Air capacity of 480m<sup>3</sup>/h
- For environments of up to 450m<sup>3</sup>
- Low temperature operation -10 to +35°C
- Low humidity operation down to 10% relative humidity
- Ventilation only mode available – if preset humidity level is exceeded, normal dehumidification mode starts (only with optional external hygostat)
- Sturdy unit made of stainless steel and powder coated sheet steel, supported by four rubber non-marking feet
- Integrated lifting handle and stackable design for easy use
- The rotor unit is easy to remove for cleaning purpose
- Dynamic, safe and self-regulating PTC heating element
- Energy-efficient radial fan
- High-performance ECODRY G3-MH rotor for maximum water absorption
- Air filter on the process air inlet
- Noise reduced via integrated silencer: 60 dB
- Connection for external hygostat
- Non-resettable hour counter
- Optional MID approved kWh meter


### Optional accessories



**Regeneration air outlet**  
Thermaflex hose  
80 mm  
6000-0004



**Dry air outlet**  
Superflextract  
hose 125  
6000-0012



**Spare filter**  
5107-0073



**External hygostat**  
6109-0040

## PORTABLE DRYING

# HIGH-PERFORMANCE ADSORPTION DRYER FOR LOW TEMPERATURE AREAS

Despite weighing out at just 25 kilos, the ASE 400 is the right choice for applications that require an air change of up to 480m<sup>3</sup>/h (environments of up to 450m<sup>3</sup>). That's 20% more than other units of comparable size that are currently on the market.

With its integrated lifting handle and stackable design, the unit has been designed for easy handling and transportation. It comes with a built-in hour counter with an optional MID-approved energy counter. The portable adsorption dehumidifiers can run continuously, or they can be controlled by an external hygrostat.

Specifications	Units	ASE 400
Capacity (20°C/60% RH)	kg/24h	36
Efficiency	l/kWh / kWh/l	0.80/1.26
Air volume – dry air/regeneration air	m <sup>3</sup> /h	480/185
Ext. pressure – dry air	Pa/m <sup>3</sup> /h	100/465, 150/406, 200/350
Ext. pressure – regeneration air	Pa/m <sup>3</sup> /h	100/172, 150/155, 200/128
Operating temperature range	°C	-10 - +35
Operating humidity range	%	10-95
Nominal power consumption	W	2,000
Power supply	V/Hz	230/1ph/50
Power cord	m	4.5
Sound level	dB(A)	60
Protection		IP23
<b>Duct sizes:</b>		
Air inlet		Process and regeneration air together with air filter
Dry air outlet	Ømm	125
Regeneration air outlet	Ømm	80
Product size (h x w x d)	mm	410 x 395 x 560
Weight	kg	25


## Applications




Archives




Cellars




Construction sites



Garages



Production facilities



Warehouses & storage facilities



Waterworks



Water Damage Restoration

**Dantherm A/S**

Marienlystvej 65  
DK-7800 Skive  
Denmark  
t. +45 96 14 37 00

**Dantherm Ltd.**

Unit 12, Galliford Road  
Maldon CM9 4XD  
United Kingdom  
t. +44 (0)1621 856611

**Dantherm GmbH**

Oststraße 148  
22844 Norderstedt  
Germany  
t. +49 40 526 8790

**Dantherm S.p.A.**

Via Gardesana 11  
37010 Pastrengo (VR)  
Italy  
t. +39 045 6770533

**Dantherm Sp. z o.o.**

ul. Magazynowa 5a  
62-023 Gądk  
Poland  
t. +48 61 65 44 000

**Dantherm SP S.A.**

C/Calabozos 6  
(Polígono Industrial)  
28108 Alcobendas, Madrid  
Spain  
t. +34 91 661 45 00

**Dantherm SAS**

23 rue Eugène Hénaff  
69694 Vénissieux Cedex  
France  
t. +33 4 78 47 11 11

**Dantherm AS**

Løkkeåsveien 26  
3138 Skallestad  
Norway  
t. +47 33 35 16 00

**Dantherm AB**

Fridhemsvägen 3  
602 13 Norrköping  
Sweden  
t. +46 (0)11 19 30 40

**Dantherm LLC**

Transportnaya 22/2  
142800, Stupino  
Moscow  
Russia  
t. +7 (495) 642 444 8

**MCS China**

Unit 2B, No. 512  
Yunchuan Road  
Baoshang, Shanghai, 201906  
China  
t. +8621 61486668

**AirCenter AG**

Täferstrasse 14  
CH-5405 Baden Dättwil  
Switzerland  
t. +41 43 500 00 50

**Heylo GmbH**

Im Finigen 9  
28832 Achim  
Germany  
t. +49 4202 97550

**SET Energietechnik GmbH**

August-Blessing-Straße 5  
71282 Hemmingen  
Germany  
t. +49 7150 94540

Dealer:

KEEP UPDATED  
**FOLLOW US ON:**



[danthermgroup.com](http://danthermgroup.com)